



Performance Tires

Mickey Thompson Performance Tires & Wheels, produces leading edge racing and high performance tires for drag racing cars and motorcycles, modified street cars, off-road race vehicles, modified pick-up trucks and sport utility vehicles. Founded in 1963 by racing legend Mickey Thompson, we offer a wide range of tires and wheels in unique sizes to enhance the look and performance of these high performance and racing vehicles, on asphalt or off!

SPORTSMAN S/R™ RADIAL

Mickey Thompson unveils the modern day version of the classic Sportsman tire. This version features performance and appearance benefits with radial construction for improved handling, better mileage, and a smoother ride and a unique flamed tread pattern for a look that says "Performance!". Note; These are radial tires, it is never recommended that Radial and non-radial tires be mixed on the same vehicle.

Sportsman S/R™ Fronts

SIZE	WEIGHT	RIM	TREAD WIDTH	PART NO.
24 x 5.00R15LT	15	3.5-4.5	4.5	6651
26 x 6.00R15LT	20	3.5-5	5.7	6652
26 x 8.00R15LT	20	5-7	7.0	6650
24 x 5.00R18LT	14	3.5-4.5	4.5	6681
26 x 6.00R18LT	18	4.5-5.5	5.7	6682
26 x 8.00R18LT	21	6-7	7.2	6680

Sportsman S/R™

SIZE	WEIGHT	RIM	TREAD WIDTH	OVERALL DIA.	PART NO.
26 x 10.00R15LT	23	7-9	8.8	26.1	6653
26 x 12.00R15LT	26	8.5-11	10.6	26.1	6654
28 x 10.00R15LT	27	7-8.5	8.7	28.0	6640
29 x 15.00R20LT	41	13-14	13.0	29.0	6620
29 x 18.00R15LT	49	14-16	15.8	29.0	6655
30 x 12.00R15LT	36	8.5-10	10.2	30.0	6643
30 x 12.00R18LT	36	9-11	10.2	29.9	6672
31 x 16.00R20LT	47	12-14	13.5	31.0	6621
31 x 18.00R15LT	50	14-16	15.7	31.0	6656
33 x 22.00R15LT	59	15-18	17.8	32.0	6657
29 x 18.00R18LT	49	15-16	15.8	29.0	6685
31 x 18.00R18LT	50	14-16	15.8	31.0	6686
29 x 18.00R20LT	46	15-16	15.5	29.0	6625
31 x 18.00R20LT	50	15-16	15.7	31.1	6626



ET STREET™

• Nylon, Black, Tubetype • D.O.T. Approved • Wrinkle Wall • Warning-ET Street tires have passed D.O.T. requirements but have reduced tread depth & compounds designed for racing only. Due to the reduced tread depth, these tires should be used on dry pavement only & are not suitable for normal highway use. Not all sizes listed. All tires compound M-5.

SIZE	TREAD	SUGGESTED TUBE SIZE	DIAMETER	CIRCUM.	PART NO.
26 x 10.50-15LT	8.3	9553	26.1	82	3752
26 x 10.50-15	9.8	9553	26.3	82	3753
26 x 10.50-16	8.4	9553	25.9	82	3792
27 x 10.50-15LT	8.9	9553	27.0	85	3758
28 x 11.50-15	8.6	9553	27.6	87	3754
28 x 12.50-15LT	10	9555	28.1	88	3755
28 x 13.50-15	11	9555	28	88	3757
30 x 12.50-15LT	10.2	9555	30	94	3762
30 x 13.50-15	11.1	9555	30	94	3763
32 x 17.50-15	14.2	9558	32.2	101	3774
33 x 18.50-15LT	15.8	9558	33.3	104	3780
26 x 11.50-16	9.7	9553	26.2	82	3793
26 x 11.50-17LT	9.5	Tubeless	26.5	83	3743

RACING TUBES

Made Specifically For High Performance Racing Applications

100% natural rubber tubes with an aircraft style removable valve stem that clamps to the wheel. Extremely light weight and durable, these tubes are a must for racing applications. Natural rubber is far superior to other materials because of its ability to conform to sidewall distortion and its resistance to deterioration due to many heat cycles.

PART NO.	APPROX. WEIGHT	SIZE	APPLICATION
9553	3.6	9.00-15	24.5 to 28" diameter tires with 8 to 10.5" tread width
9555	5.1	11.00-15	28 to 31" diameter tires with 10.5 to 11.5" tread width
9558	7.0	15.00-15/16	31 to 33.5" diameter tires with 12 to 17" tread width



Performance Tires

Mickey Thompson Performance Tires & Wheels, produces leading edge racing and high performance tires for drag racing cars and motorcycles, modified street cars, off-road race vehicles, modified pick-up trucks and sport utility vehicles. Founded in 1963 by racing legend Mickey Thompson, we offer a wide range of tires and wheels in unique sizes to enhance the look and performance of these high performance and racing vehicles, on asphalt or off!



ET STREET™ RADIAL

• Polyester Ply, Steel Belted Radial, Black, Tubeless • Soft Drag Tire Compound for Superior Traction on the Drag Strip • D.O.T Approved, Street Legal • Special Sidewall Construction for Quick Launches • Low Void Directional Tread Pattern Eliminates Feathering

SIZE	SIZE EQUIVALENT	TREAD	DIAMETER	CIRCUM.	RIM	PART NO.
235/60R15	26.0/9.5-15	8	26.1	82	8	3752R
255/60R15	27.0/10.5-15	8.8	27	85	8	3756R
275/50R15	26.0/11.5-15	10	26.1	82	10	3753R
275/60R15	28.0/11.5-15	8.9	28	87	8	3754R
295/65R15	30.0/12.5-15	10	29.6	94	10	3762R
315/60R15	30.0/13.5-15	11	29.8	94	10	3763R
325/50R15	28.0/13.5-15	11	27.9	88	10	3757R
255/50R16	26.0/10.5-16	9.7	26.1	82	10	3793R
275/40R17	26.0/11.5-17	10.2	25.7	82	9	3743R



**World's
Fastest
Street
Radial!**

ET DRAG™

• Nylon, Black, Tubetype • A Proven Dragstrip Winner • Compounded for Longer Life • Engineered for Consistent Performance • Requires Little or No Burn Out

PART NO.	SIZE	COMPOUND	APPROX.		SUGGESTED SIDEWALL		TREAD		DIA.	CIRCUM.
			WGT.	RIM	TUBE	WIDTH	WIDTH			
3014	24.5/8.0-13	L8	16	8	9553	10.5	7.7	24.5	77	
3020	26.0/8.5-14	L8	18	8	9553	10.2	8.2	26.0	82	
3024	28.0/9.0-14	L8	21	8	9553	11.0	8.5	27.2	86	
3052	26.0/8.5-15	L8	19	7	9553	9.5	8.1	25.9	82	
3053	26.0/10.0-15	L8	22	9	9553	11.0	9.6	26.0	82	
3054	28.0/9.0-15	L8	22	8	9553	10.8	8.6	27.3	88	
3055	28.0/10.5-15	M5	23	9	9553	11.7	10.0	28.1	88	
3057	28.0/11.5-15	M5	27	10	9555	12.9	11.0	28.0	88	
3056	29.5/9.0-15	L8	22	8	9553	11.4	8.7	29.6	93	
3062	29.5/10.5-15	M5	25	9	9555	12.4	10.2	29.9	94	
3062W	29.5/10.5-15W	M5	30	10	9555	13.6	11.2	29.6	93	
3064	29.5/11.5-15	M5	27	10	9555	13.6	11.1	29.9	94	
3068W	31.0/10.5-15W	M5	33	10	9555	14.5	10.8	31.3	99	
3072	31.0/13.0-15	M5	32	12	9558	15.7	13.0	30.8	97	
3074	32.0/14.0-15	L8	34	14	9558	17.2	14.2	32.2	101	
3074S*	32.0/14.0-15	T5	33	14	9558	17.1	14.2	32.2	101	
3075	32.0/14.5-15	L8	38	14	9558	18.0	14.8	32.5	103	
3076S	32.0/16.0-15	L8	35	15	9558	18.5	15.8	32.0	101	
3079	33.0/15.0-15	L4	37	14	9558	18.1	14.8	32.6	103	
3084	33.0/15.0-15	L4	39	15	9558	20.0	16.7	33.5	105	
3084S	33.0/15.0-15	L8	41	15	9558	20.0	16.7	33.5	105	
3186	34.5/17.0-16	M5	45	16	*	21	17.0	35	110	

S indicates Stiff sidewall. W indicates extra wide tread area. Acceptable practice for rim width is tread with plus or minus 1 inch. All dimensions at 10 psi cold on measuring rim. *Must run innerliner or beadlocks.



ET FRONTS™

• Nylon, Black • Ultra Lightweight Design Reduces Rolling Resistance.

PART NO.	SIZE	APPROX. WGT.	RIM	SIDEWALL WIDTH	TREAD WIDTH	DIA.	CIRCUM.
3005	22.5/4.5-15	7	3.5-5.0	5.1	4.1	22.5	71
3004	24.5/8.0-13	4	2.5	2.7	1.5	22.0	67
3003	25.0/4.5-15	11	3.5-5.0	6.7	5.0	25.3	79
3006*	26.0/8.5-14	11	3.5-5.0	6.3	4.7	23.8	75
3007*	28.0/9.0-14	12	3.5-5.0	6.3	4.7	25.9	81
3009*	26.0/10.0-15	14	3.5-5.0	6.1	4.5	27.5	86

*Approved for Bonneville use. Call for speed rating.



Some parts are not legal for sale or use in California on any pollution controlled motor vehicle.



Moroso's deep ties to racing has made it a company of firsts; the first to make oil pans with deep and kicked-out sumps, the first tall valve cover, lightweight front drag tires, electric water pump drives, the four-link, the racing vacuum pump, the racing crank trigger, the racing electric water pump, "Trick" coil springs. All of these products had their origins at Moroso. Moroso's goal is to help you solve your problems, run faster and win races.

DS-2™ FRONT TIRES

Why waste valuable horsepower "pushing" a street tire down the track? Engineered specifically for racing, these tires are ultra-light to reduce unsprung weight and rolling resistance. Our new DS-2™ tires use an innovative, aircraft-inspired tread that provides low rolling resistance on acceleration, and a broader footprint during braking. And each tire is 100% inspected for defects, even the slightest blemish causes the tire to be rejected.



DESCRIPTION	PART NO.
24.0 x 5.0-15	17040
25.0 x 4.5-15	17025
26.0 x 4.5-15	17026

TIRE COVERS

Keeps tire pressures consistent by blocking hot rays. Made from a rugged 6 mil vinyl reflecting outer surface laminated to an insulating backing of polyscrim.



DESCRIPTION	PART NO.
Fits over tires up to 33.5 x 17.5-15	99410
Universal design with suction cups, 42" x 36"	99421

SELF-EJECTING FASTENERS

These spring-loaded buttons guarantee a quick release. The spring holds the button captive so that it can't be dropped underneath the car or into some hard-to-get-at area of the chassis. 10/package.



DESCRIPTION	PART NO.
.500" medium, grip range .198"-.233"	71500
.650" long, grip range .348"-.383"	71530

BUTTERFLY SELF-EJECTING FASTENERS

These fasteners eliminate the need for tools. Same as self-ejecting fasteners except with thumb screw on top. 10 per package.



DESCRIPTION	PART NO.
.500" medium, grip range .198"-.233"	71510
.650" long, grip range .348"-.383"	71540

QUICK FASTENER WRENCH

Part No. 71600



WHEEL STUDS

Moroso Wheel Studs are manufactured from high grade SAE 8740 steel to withstand shear loads of 190,000 psi. Wheel Studs are designed expressly for use with thick-hub racing wheels for both drag and oval track racing. All Moroso Press-In Type Wheel Studs now feature a "quick start dog end" for easier starting of lug nuts. Packed in sets of five.



DESCRIPTION	PART NO.
7/16" - 20 X 2-7/8" Press-In, .480" dia. knurl and quick start dog end fits most late GM drum brake applications,	46150
7/16" - 20 X 2-7/8" Press-In, .560" dia. knurl and quick start dog end fits most late GM disc and early drum brake applications	46160
1/2" - 20 x 3" Press-In, .615" dia. knurl and quick start dog end fits most disc brake Fords front and rear & Chrysler front	46180
1/2" - 20 x 3" Press-In, .594" dia. knurl and quick start dog end fits 79-03 Mustang. Also has flat on head for front heads with ABS. Standard hole size: .580"	46185
1/2" - 20 x 3" Press-In, .685" dia. knurl and quick start dog end fits most Chrysler rear with 1/2" stud	46190
1/2" - 20 x 3" Press-In, .563" dia. knurl and quick start dog end for use 1/2" Frankland hubs	46220
5/8" - 18 x 3" Press-In, .672" dia. knurl and quick start dog end for oval track applications	46240
1/2" - 20 x 3" Screw-In, fits all aftermarket axles with 1/2"-20 threads	46200

QUICK FASTENER MOUNTING BRACKETS

Brackets can be welded or fastened to any member of the car to provide a convenient pop rivet mount for self-ejecting fastener springs. 10 per package.



DESCRIPTION	PART NO.
Use with No.71430 or 71425 Spring	71550
Flat Mounting Bracket	71551
90° Angle Bracket	71552
Heavy Duty Bracket (2 per package)	71555

REPLACEMENT FASTENER SPRINGS

Designed for use with Moroso's flat, oval head and butterfly fasteners. 10 per package.



DESCRIPTION	PART NO.
1" Spring (.325" spring height)	71430
1-3/8" Spring (.325" spring height)	71420
1-3/8" Spring (.425" spring height)	71400

HEAVY DUTY QUICK FASTENER WRENCH

Part No. 71600



WHEEL RIM SCREWS

Manufactured from rugged Grade 8 steel to withstand the extreme loading placed on today's racing tires. Self-tapping screws feature built-in washer face for maximum holding strength. Finished in gold iridite. 1/4" dia. x 3/4" long. 35 per pack.



Part No. 90100

TIRE PRESSURE GAUGE

Individually calibrated for accuracy within 2%. The large 2-5/8" diameter dial face is easy to read, while the hardened swivel chuck rotates 360° for positive valve stem attachment. A finger operated air-bleed valve allows you to release pressure quickly.



Part No. 89550 0-15 PSI

OFFSET ROLL BAR PADDING

Our popular Roll Bar Padding is now packaged in single 3-foot lengths for improved convenience and pricing. 3" O.D. padding is extruded from high-density foam for maximum safety and protection.



DESCRIPTION	PART NO.
Offset Roll Bar Padding, Black	80939
Offset Roll Bar Padding, Blue	80940
Offset Roll Bar Padding, Red	80941
Offset Roll Bar Padding, Orange	80942



Tire & Wheel Accessories

The Mr. Gasket brand provides a variety of performance and racing products for all parts of your vehicle including: carburetor and fuel accessories, chrome-plated accessories, cooling system accessories, engine components, ignition and electrical accessories, shifter accessories, specialty tools and suspension and driveline components.

COMPETITION WHEEL STUDS

Extra long, press-in and screw in studs. Made of high quality grade 8 material and are plated for durability. NHRA approved. 10/set.



DESCRIPTION	PART NO.
7/16"-20 x 2-5/8" fits 63-75 Chevy	4310G
1/2"-20 x 2-7/8" fits Chrysler, Ford and most 1/2" applications	4311
12-point washer head, 1/2"-20 x 3" fits all axles w/1/2"-20 thread	4312

COMPETITION OPEN-END LUG NUTS

Chrome lug nut has an open-end feature that allows you to inspect thread depth. It fits most popular mag wheels & stud diameters. Approved by major racing associations. 5/set.



DESCRIPTION	PART NO.
7/16" RH rear, 3/4" shank	4300G
1/2" RH, rear, 3/4" shank	4301G
7/16" RH, Cragar Super Trick, front, 1 3/8" shank	4302G
1/2" RH, Cragar Super Trick, front, 1 3/8" shank	4303G

TIRE SCREW KIT

Made from grade 8 steel to withstand the extreme loading encountered when launching on today's concrete starting pads. Kit contains 35 hex head screws to complete 2 wheels. Drill bit included.

Part No. 4318



SELF-ADHESIVE WHEEL WEIGHTS

Easily installed, these weights fit any sport or competition wheel. No fasteners are necessary; no tools required with the self-adhesive back. Two inches equal one ounce. (Four 4" strips)

Part No. 1428



WHEEL DUST COVERS

Conceals rusty brake components and stops unsightly brake dust. Formed from high quality, black aluminum, can be painted to color co-ordinate with any vehicle. Will not fit most front wheel drive. 2 per set.



DESCRIPTION	PART NO.
15" 5 4 1/2" thru 5"	6905
16" 5 4 1/2" thru 5"	6906

BABY MOON HUB CAPS

Add a touch of class to your stock wheels. These hub caps are made of strong steel to resist denting and are chrome-plated for lasting beauty. 4/set.

Part No. 4580 Most GM and Ford w/stock 14"/15" stock wheels



DISC BRAKE WHEEL SPACERS

Constructed from die-cast aluminum, wheel spacers provide the necessary clearance for mag or chrome wheel applications. 2 per kit.



DESCRIPTION	PART NO.
7/32" Thick, 4 1/2"-5" bolt circle	2370
5/16" Thick, 4 1/2"-5" bolt circle	2371
7/16" Thick, 4 1/2"-5" bolt circle	2372
1/4" Thick, Datsun, Toyota, Pinto, Vega, Maverick, 4"-4 1/4" bolt circle	2375
1/4" Thick, Chevy truck 6 bolt, 5 1/2" bolt circle	2376
1/4" Thick, Ford, Dodge truck 8 bolt, 6 1/2" bolt circle	2377

CHROME VALVE STEM CAPS

Replace stock plastic caps or stolen custom caps. 4/set.

Part No. 3663



STRAIGHT CHROME TIRE VALVES

Heavy chrome plating & quality finish add the classic touch to your mag or chrome rims. 4/set.

Part No. 1957



FLUSH MOUNT TIRE VALVES

Give any custom wheel a clean, smooth appearance by eliminating unsightly valve stems. Manufactured from the highest quality brass and chrome plated, these flush mount tire valves are engineered to fit all tubeless applications on most chrome, steel or aluminum wheels.

Part No. 5102



CHROME PLATED LUG NUTS

Dress up your stock or custom wheels with chrome plated lug nuts. Machined from solid steel, available with acorn style tops, tapered or mag-shank ends.



THREAD	ACORN	9/16' MAG SHANK	1-1/16" MAG
7/16"	1440	1740	1760
1/2"	1441	1741	1761
12mm x 1.5 RH	1444	---	---

WHITE TIRE MARKER

Molded oil based paint stick resists weather, washing and peeling off.

Part No. 9312

